



型号 MODEL NO.	主要尺寸 MAIN DIMENSIONS					安装尺寸 Mounting dimension								基本额定载荷 BASIC LOAD RATING		刚性 RIGIDITY (Kgf/um)
	螺杆 外径 SCREW DIAMETER	导程 THREAD DISTANCE	钢珠 外径 BALL DIAMETER	螺帽 外径 NUT OUTER DIAMETER	珠圈 数 BALL CIRCULATION Number									C(kgf)	Co(kgf)	
	d	s	Da	D	n	Q	A	G	H	L	B	W	d1	K		
SFUR 1605	16	5	3.175	28	3	M6	48	44	40	50	10	38	5.5	780	1790	20
SFUR 2005	20	5	3.175	36	3	M6	58	51	44	51	10	47	6.6	1130	2380	25
SFUR 2505	25	5	3.175	40	3	M8	62	55	48	51	10	51	6.6	1280	3110	35
SFUR 3205	32	5	3.175	50	3	M8	80	71	62	52	12	65	9	1450	4150	40
SFUR 3210		10	6.35	50	3	M8	80	71	62	90	12	65	9	3390	7170	40
SFUR 4005	40	5	3.175	63	3	M8	93	81.5	70	55	14	78	9	1610	5350	49
SFUR 4010		10	6.35	63	3	M8	93	81.5	70	93	14	78	9	3910	9520	50
SFUR 5010	50	10	6.35	75	3	M8	110	97.5	85	93	16	93	11	4450	12500	65
SFUR 6310	63	10	6.35	90	3	M8	125	100	95	98	18	108	11	5070	16600	80
SFUR 8010	80	10	6.35	105	3	M8	145	127.5	110	98	20	125	13.5	5620	21300	90